

JAS ASSOCIATES

J250N Technical Specification

Product Image



| | |
|-----------------------------------|---------------|
| Model | J250N |
| Dispenser Flow Rate | 250 liters/Hr |
| Storage Tank-HOT-Water | |
| Storage Tank-Cold-Water | |
| Storage Tank-Normal Water | 100 Liters |
| No. of Faucets | 3 or 4 or 7 |
| Heater Power in Watts | |
| Cooler Power in Watts | |
| Nett Weight in Kg (Approx) | 68 |

| | |
|--------------------------------------|---|
| Water Purification Technology | |
| Inlet Water TDS Recommended | |
| Purification Stages | |
| Input Water TDS Rejection | |
| Recovery | |
| Power Supply (AC 50Hz) | 180 to 240 V AC/50 Hz |
| Control Type | Float Switch /Float Valve |
| MOC-Housing | Stainless Steel 202 Grade -0.8 mm thick |
| MOC-Normal Storage Tank | LLDPE or SS304 Grade-0.8mm thick |
| MOC-Hot Storage Tank | |
| MOC-Cold Storage Tank | |
| MOC-Faucets | Brass Chromium plated |
| MOC-Heater Coil | |
| MOC-Drip Tray | Stainless Steel 304Grade-0.8mm thick |
| MOC-Leg | Stainless Steel 304Grade-2mm thick |
| MOC-Rear Cover | Stainless Steel 202 Grade -0.8 mm thick |
| Cooling Temperature Range | |
| Heater Temperature Range | |
| Condenser Tubing | |
| Insulation of Cooling Tank | |
| Compressor Make | |
| Compressor Refrigerant | |
| Dimension-Model | L-600mm, B-700mm , H-1475mm |

Contact Details

Website : <https://jasassociates.org>