JAS ASSOCIATES

J80NRO Technical Specification

Product Image

new

Image not found or type unknown

Model	J80NRO
Dispenser Flow Rate	80 liters/Hr
Storage Tank-HOT-Water	
Storage Tank-Cold-Water	
Storage Tank-Normal Water	30 Liters
No. of Faucets	1 or 2
Heater Power in Watts	
Cooler Power in Watts	
Nett Weight in Kg (Approx)	40
Water Purification Technology	RO
Inlet Water TDS Recommended	Borewell Water- 300PPM to 1800PPM(Max)
Purification Stages	Fine Sediment Filter, Activated Carbon Filter, RO Membrane, Post Carbon Filter, UV(Optional)
Input Water TDS Rejection	90%
Recovery	30-40%
Power Supply (AC 50Hz)	180 to 240 V AC/50 Hz
Control Type	Float Switch /Float Valve
MOC-Housing	Stainless Steel 202 Grade -0.8 mm thick
MOC-Normal Storage Tank	LLDPE or SS304 Grade-0.8mm thick
MOC-Hot Storage Tank	

MOC-Cold Storage Tank	
MOC-Faucets	Brass Chromium plated
MOC-Heater Coil	
MOC-Drip Tray	Stainless Steel 304Grade-0.8mm thick
MOC-Leg	Stainless Steel 304Grade-2mm thick
MOC-Rear Cover	Stainless Steel 202 Grade -0.8 mm thick
Cooling Temperature Range	
Heater Temperature Range	
Condenser Tubing	
Insulation of Cooling Tank	
Compressor Make	
Compressor Refrigerant	
Dimension-Model	L-360mm, B-370mm , H-1375mm

Contact Details

Website : https://jasassociates.org