

JAS ASSOCIATES

J300NHC Technical Specification

Product Image



Model	J300NHC
Dispenser Flow Rate	300 liters/Hr
Storage Tank-HOT-Water	5 Liters
Storage Tank-Cold-Water	60 Liters
Storage Tank-Normal Water	60 Liters
No. of Faucets	3 or 4 or 7
Heater Power in Watts	1000
Cooler Power in Watts	1000
Nett Weight in Kg (Approx)	84

Water Purification Technology	
Inlet Water TDS Recommended	
Purification Stages	
Input Water TDS Rejection	
Recovery	
Power Supply (AC 50Hz)	180 to 240 V AC/50 Hz
Control Type	Float Switch /Float Valve
MOC-Housing	Stainless Steel 202 Grade -0.8 mm thick
MOC-Normal Storage Tank	LLDPE or SS304 Grade-0.8mm thick
MOC-Hot Storage Tank	Stainless Steel 304 Grade-0.8mm thick
MOC-Cold Storage Tank	Stainless Steel 304 Grade-0.8mm thick
MOC-Faucets	Brass Chromium plated
MOC-Heater Coil	Stainless Steel
MOC-Drip Tray	Stainless Steel 304Grade-0.8mm thick
MOC-Leg	Stainless Steel 304Grade-2mm thick
MOC-Rear Cover	Stainless Steel 202 Grade -0.8 mm thick
Cooling Temperature Range	16 to 22Â°C(Thermostat Adjustable)
Heater Temperature Range	40 to 80Â°C(Thermostat Adjustable)
Condenser Tubing	Grooved Copper
Insulation of Cooling Tank	Polyurethane Foam-50mm thick
Compressor Make	Emerson/Tecumseh
Compressor Refrigerant	R-134a
Dimension-Model	L-600mm, B-700mm , H-1475mm

Contact Details

Website : <https://jasassociates.org>